Page 1 of 7



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

Product Name: Canon Starter (Yellow) for CLC1100 series

Product Code: 1473A / F42-3132

Company Name: Canon Inc.

Address: 30-2, Shimomaruko 3-Chome, Ohta-ku, Tokyo 146-8501, Japan

Use of the Product: Toner for electrophotographic apparatus

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

| < | Ingredient | (s |) > | |
|---|------------|----|-----|--|
| | | | | |

| Chemical Name / Generic Name | CAS#/ EC# | Weight % | EU Symbol/ R-Phrase | USA OSHA PEL | ACGIH TLV | EU ILV | DFG MAK |
|---------------------------------|----------------|----------------------------|------------------------|--|--|-----------------|---|
| Ferrite including manganese | Not registered | 90-95 (as Mn: 16-18) | None/ None | 5 mg/m³ (Ceiling) Manganese compounds (as Mn) | 0.2 mg/m³ (TWA) Manganese elemental, and inorganic compounds, as Mn | Not established | 0.5 mg/m² (Inhalable fraction) Manganese and its inorganic compounds |
| Polyester resin | Confidential | 5-10 | None/ None | Not established | Not established | Not established | Not established |

< Carcinogen >

Chemical Name CAS # Reference

No component of this toner is listed as a human carcinogen or a potential carcinogen in IARC Monographs, NTP, OSHA regulations or Annex I to Directive 67/548/EEC.

SECTION 3 HAZARDS IDENTIFICATION

EU Classification:

Not classified as dangerous.

Emergency Overview:

Yellowish gray fine powder, slight plastic odor.

Inhalation of excessive amount of manganese powder may cause cough, shortness of breath or pneumonitis.

Potential Health Effects and Symptoms:

Inhalation:

Exposure to excessive amounts of dust may cause physical irritation to respiratory tract.

Ingestion:

Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Eye:

May cause transient slight irritation.

Skin:

May be non-irritant.

Chronic Effects:

Prolonged inhalation of excessive amounts of manganese powder may cause lung damage and nervous system effects. Normal use and handling of this product does not result in inhalation of excessive amounts of manganese powder.

Medical Conditions Generally known to be Aggravated by Exposure:

Not determined



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

SECTION 4 FIRST AID MEASURES

First Aid Measures:

Inhalation:

If symptoms are experienced, move victim to fresh air and obtain medical advice.

Ingestion:

Rinse mouth. Drink 1 or 2 glasses of water. If irritation or discomfort occurs, obtain medical advice immediately.

Eye:

Do not allow victim to rub eye(s). Flush with lukewarm, gently flowing water for 5 minutes or until particle is removed. If irritation persists, obtain medical attention.

Skin:

Wash with soap and water. If irritation persists, obtain medical advice.

Note to Physicians:

None

SECTION 5 FIRE FIGHTING MEASURES

Fire Fighting Measures:

Extinguishing Media:

CO2, water, dry chemicals

Unsuitable Extinguishing Media:

None

Special Fire Fighting Procedures:

None

Unusual Fire and Explosion Hazards:

Can form explosive dust-air mixtures when finely dispersed in air.

Fire and Explosive Properties (See also Section 9):

Hazardous Combustion Products:

CO2, CO

Other Properties:

Not available

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Do not breathe dust.

Wash thoroughly after handling.

Environmental Precautions:

Do not wash away into sewer.

Method for Cleaning Up:

Sweep slowly spilled powder on to paper, and carefully transfer into a waste container. Clean remainder with wet paper, wet cloth or a vacuum cleaner.

If a vacuum cleaner is used, it must rate as a dust explosion-proof type. Fine powder can form explosive dust-air mixtures.

SECTION 7 HANDLING AND STORAGE

Handling:

Avoid breathing dust.

Use with adequate ventilation.

Storage:

Keep out of the reach of children.

Keep away from oxidizing materials.

Specific Uses:

Toner for electrophotographic apparatus.

For more information, please refer to the instruction of this product.

Page 3 of 7



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

EXPOSURE CONTROLS / PERSONAL PROTECTION SECTION 8 Exposure Guidelines: USA OSHA PEL (TWA): 15 mg/m³ (Total dust), 5 mg/m³ (Respirable fraction) 10 mg/m³ (Inhalable fraction), 3 mg/m³ (Respirable fraction) ACGIH TLV (TWA): DFG (MAK): 4 mg/m³ (Inhalable fraction), 1.5 mg/m³ (Respirable fraction) (Also refer to SECTION 2) **Engineering Controls:** Use adequate ventilation. **Personal Protection Equipment(s): Respiratory Protection:** Required ■ Not Required **Eye/Face Protection:** ☐ Required **☒** Not Required **Skin Protection:** ☐ Required **☒** Not Required **SECTION 9** PHYSICAL AND CHEMICAL PROPERTIES Yellowish gray fine powder **Appearance:** Odor: Slight plastic odor pH: Not applicable Boiling Point/Range(°C): Not applicable Melting Point/Range(°C): 85-120 (Softening point) **Decomposition Temperature(°C):** > 200 Flash Point(°C): Not applicable Not applicable Flammable (Explosive) Limits: **Autoignition Temperature(°C):** Not available Flammability: Not-flammable (Test method: Directive 92/69/EEC, A10 Flammability **Explosive Properties:** Can form explosive dust-air mixtures when finely dispersed in air. **Oxidizing Properties:** Not available Vapor Pressure: Not applicable Vapor Density: Not applicable **Density / Specific Gravity:** 4.0-6.0 Water Solubility: Negligible Partially soluble in toluene and xylene. **Fat Solubility:** Partition Coefficient (n-Octanol/Water): Not applicable **Percent Volatile:** Negligible **Evaporation Rate:** Not applicable Viscosity (mPa s): Not applicable

Page 4 of 7



lung for a prolonged interval.

MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

| SECTION 10 STABILITY AND | REACTIVITY |
|---|---|
| Stability: | Stable Unstable Unstable |
| Conditions to Avoid: | None |
| Materials to Avoid: | Strong oxidizers |
| Hazardous Decomposition Products: | CO, CO2 |
| Hazardous Polymerization: | ☐ May Occur ☑ Will Not Occur |
| Conditions to Avoid: | None |
| SECTION 11 TOXICOLOGICA | AL INFORMATION |
| Acute Toxicity: Inhalation: Not available | |
| Ingestion: Estimate: Rat, LD50 > 2000 mg/ | kg (See Section 16) |
| Eye: Estimate: Rabbit, transient slight | conjunctival irritation only. (See Section 16) |
| Skin: Estimate: Rabbit, non-irritant (Se | ee Section 16) |
| Sensitization: Not available | |
| Mutagenicity: Estimate: Ames Test (S. typhimu | urium): Negative (See Section 16) |
| Reproductive Toxicity: | |
| Manganese and its inorganic con There is a study showing that pro adverse effects on the fertility of | npounds: slonged inhalation of excessive amounts of manganese powder may cause male workers. However, normal use and handling of this product, as intended, accessive amounts of manganese powder. |
| Carcinogenicity: Not available | |
| Others: | |
| Chronic effects: Muhle et al. reported pulmonary respirable-sized particles compar most relevant to potential human at 4 mg/m³, and a mild to modera | response upon chronic inhalation exposure in rats to a toner enriched in red to commercial toner. No pulmonary change was found at 1 mg/m³ which is exposure. A minimal to mild degree of fibrosis was noted in 22% of the animals at degree of fibrosis was observed in 92% of the animals at 16 mg/m³. These verloading", a generic response to excessive amounts of any dust retained in the |

Page 5 of 7



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

| SECTION 12 E | COLOG | SICAL INFORMATION |
|---|----------------------------------|--|
| Mobility: | | Not available |
| Persistence / Degrad | lability: | Not available |
| Bioaccumulation: | | Not available |
| Ecotoxicity: | | Not available |
| Other Adverse Effec | cts: | Not available |
| SECTION 13 | DISPOSA | L CONSIDERATIONS |
| Method of Disposal: Disposal should b | | to federal, state and local laws. |
| SECTION 14 | ΓRANSP | ORT INFORMATION |
| UN #: | None | |
| UN Shipping Names | None | |
| UN Classification: | None | |
| UN Packing Group: | None | |
| Marine Pollutant: | ☐ Yes ⋈ No | Chemical name (wt%): |
| | | |
| Special Precautions | _ | |
| | : None | TORY INFORMATION |
| SECTION 15 | None | TORY INFORMATION |
| | None | TORY INFORMATION |
| SECTION 15 F < EU Information > | None REGULA Label: | |
| SECTION 15 F < EU Information > Information on the | None REGULA Label: | |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: | None REGULA Label: | |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: Not required S-Phrase: | : None REGULA Label: ation: No | ot required |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: Not required S-Phrase: Not required Dangerous Com Not required | None REGULA Label: ation: No | ot required |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: | None REGULA Label: ation: No | ot required): |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: | None REGULA Label: ation: No | ot required): r 1999/45/EC Annex V: ion to Protection of Man or the Environment: |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: Not required S-Phrase: Not required Dangerous Com Not required Special Precauti Not required Specific Provisions | None REGULA Label: ation: No | ot required): r 1999/45/EC Annex V: ion to Protection of Man or the Environment: lated |
| SECTION 15 < EU Information > Information on the Symbol & Indic R-Phrase: | None REGULA Label: ation: No | to required 1: 1: 1: 1: 1: 1: 1: 1: 1: 1 |

Page 6 of 7



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

< USA Information >

Information on the Label under OSHA:

Signal Word: CAUTION!

Hazard warning:

PROLONGED INHALATION OF EXCESSIVE AMOUNTS OF MANGANESE MAY CAUSE LUNG DAMAGE AND NERVOUS SYSTEM EFFECTS.

Safety Advice:

Do not breathe dust.

Do not taste or swallow.

For additional information, see MSDS for this product.

Hazardous Component(s):

Not required

SARA Title III §313:

Chemical Name Weight % 90-95 "Manganese compounds" (as Mn) (16-18)

California Proposition 65:

Chemical Name Weight % None

< Canada Information >

WHMIS Controlled Product: Not a controlled product

< Australia Information >

Statement of Hazardous Nature: Not classified as hazardous according to criteria of NOHSC.

SECTION 16 OTHER INFORMATION

Revised information from the previous version:

Section 11 and 15

Estimate: Estimate based on test data on similar toner/developer/drum and/or the raw materials of this product.

- Literature Reference:
 U.S. Department of Labor, 29CFR Part 1910
 - U.S. Environmental Protection Agency, 40CFR Part 372
 - U.S. Consumer Product Safety Commission, 16CFR Part 1500
 - ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices
 - U.S. Department of Health and Human Services National Toxicology Program, Annual Report on Carcinogens
 - World Health Organization International Agency for Research on Cancer, IARC Monographs on the Evaluation on the Carcinogenic Risk of Chemicals to Humans
 - DFG, List of MAK and BAT Values
 - EU Directive 76/769/EEC, 67/548/EEC, 1999/45/EC
 - EU Regulation (EC)2037/2000, (EC)304/2003
 - Canada Workplace Hazardous Materials Information System
 - Australia National Occupational Health and Safety Commission's Approved Criteria for Classifying Hazardous Substances[NOHSC:1008]

Page 7 of 7



MATERIAL SAFETY DATA SHEET

MSDS #: TN1120-0403 Product Code: 1473A / F42-3132

Abbreviations:

EU: European Union.

OSHA PEL: PEL(Permissible Exposure Limit) under Occupational Safety and Health Administration (USA). ACGIH TLV: TLV(Threshold Limit Value) under American Conference of Governmental Industrial Hygienists.

EU ILV: Indicative Limit Values for Occupational Exposure under EU Directive 91/322/EEC, 2000/39/EC and 2006/15/EC.

DFG MAK: MAK(Maximale Arbeitsplatz-Konzentration) under Deutsche Forschungsgemeinschaft.

TWA: Time Weighted Average. STEL: Short Term Exposure Limit.

IARC: International Agency for Research on Cancer. NTP: National Toxicology Program (USA).

WAF: Water Accommodated Fraction

LL: Lethal Loading rate EL: Effective Loading rate

OSHA HCS: Occupational Safety and Health Act, Hazard Communication Standard (USA).

FHSA: Federal Hazardous Substances Act (USA).

WHMIS: Workplace Hazardous Materials Information System. NOHSC: National Occupational Health and Safety Commission.

The information, data and recommendations set forth herein (the "Information") are presented in good faith and are believed to be correct as of the date hereof. The company/manufacturer makes no representations as to the completeness or accuracy of the Information and disclaims responsibility for any reliance thereon. The Information is provided upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. Any use of the Information must be determined by the user to be in accordance with applicable Federal, state and local laws and regulations. In no event will the company/manufacturer be responsible for damages of any nature whatsoever resulting from the use or reliance upon the Information.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE WITH RESPECT TO THE INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS.