

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the

preparation

HP LaserJet CE390A-X-XC-XD Print Cartridge

Use of the

substance/preparation

This product is a toner preparation that is used in HP LaserJet Enterprise M4555 MFP, 600 M601,

600 M602, 600 M603 series printers.

Version No.

Revision date 07-Aug-2012

Company identification Hewlett-Packard, Ltd.

Cain Road, Amen Corner Bracknell, Berkshire, RG12 1HN Telephone 1 344 36-0000

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 **HP Customer Care Line**

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com Poison Information Center 0207771 5307

2. HAZARDS IDENTIFICATION

Acute health effects

Skin contact Unlikely to cause skin irritation. **Eye contact** May cause transient slight irritation.

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK, NTP,

OSHA or ACGIH.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC)

1907/2006.

Classification Not classified.

Physical hazards Not classified as a physical hazard. **Health hazards** Not classified as a health hazard.

Environmental hazards Not classified as an environmental hazard.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS#	Percent	EC-No.	Classification
polyester	Trade Secret	< 55		
Iron oxide	1317-61-9	< 50	215-277-5	
Amorphous silica	7631-86-9	< 3	231-545-4	

4. FIRST-AID MEASURES

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Material name: CE390A-X-XC-XD SDS UK 1/5 Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Ingestion Rinse mouth with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

General advice No additional information

5. FIRE-FIGHTING MEASURES

Fire fighting

If fire occurs in the printer, treat as an electrical fire.

equipment/instructions

Suitable extinguishing media CO2, water, or dry chemical

Extinguishing media which must not be used for safety

reasons

None known.

Unusual fire & explosion

hazards

Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.

None established.

Hazardous combustion

Specific methods

products

Carbon monoxide and carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Minimise dust generation and accumulation.

Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Other information Slowly vacuum or sweep the material into a bag or other sealed container. If a vacuum is used,

the motor must be rated as dust explosion-proof. Clean remainder with a damp cloth or vacuum cleaner. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal,

state, and local regulations.

7. HANDLING AND STORAGE

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Keep out of the reach of children. Store at room temperature. Keep tightly closed and dry. Store Storage

away from strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional exposure data USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

mq/m3

TRGS 900 (Luftgrenzwert) - 10 mg/m3 (Einatembare partikel), 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust), 5 mg/m3 (Inhalable Dust)

Use in a well ventilated area. **Exposure controls**

Occupational exposure controls

General No personal respiratory protective equipment required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Fine powder **Appearance**

Solid Physical state **Form** solid Colour Black.

Odour Slight plastic odor **Odour threshold** Not available. pН Not applicable **Boiling point** Not applicable Flash point Not applicable

Material name: CE390A-X-XC-XD

CE390A-X-XC-XD Version No.: 05 Revision date: 07-Aug-2012 Print date: 07-Aug-2012

Flammability limits in air, upper, % by volume

Not available.

Flammability limits in air,

lower, % by volume

Not flammable

Vapour pressureNot applicableRelative densityNot available.

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient

(n-octanol/water)

Not available

Not applicable **Viscosity** Vapour density Not available. Not available. **Evaporation rate Melting point** Not available. Not available. Freezing point **Auto-ignition temperature** No data available Specific gravity 1.4 - 1.8 (H2O = 1)Softening point 100 - 150 °C (212 - 302 °F)

Percent volatile Negligible
VOC Not applicable

Other information Decomposition temperature: > 200 ° C

10. STABILITY AND REACTIVITY

Conditions to avoid Imaging Drum: Exposure to light **Hazardous decomposition** Carbon monoxide and carbon dioxide.

products Stability

Stable under normal storage conditions.

Materials to avoidStrong oxidizersHazardous polymerisationWill not occur.

11. TOXICOLOGICAL INFORMATION

Oral toxicity LD50/oral/rat >2000mg/kg; Not harmful. (OECD 401). Not classified for acute oral toxicity

according to EU Directive 67/548/EEC and 1999/45/EC.

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA

Regulations (USA), EU Directive, or Proposition 65 (California).

Inhalation toxicity No information available.

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Serious eye damage/eye

irritation

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Chronic toxicity No information available.

Sensitisation Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductivity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65,

and DFG (Germany).

Further information Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aide measures.

12. ECOLOGICAL INFORMATION

Ecotoxicity LL50: > 1000 mg/l, Fish, 96.00 Hours

13. DISPOSAL CONSIDERATIONS

Disposal instructionsDo not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state,

and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

Material name: CE390A-X-XC-XD

CE390A-X-XC-XD Version No.: 05 Revision date: 07-Aug-2012 Print date: 07-Aug-2012

14. TRANSPORT INFORMATION

Further information 19 or more of these cartridges shipped together in a single package (e.g., box, container), by air,

are regulated as a magnetized material. These requirements do not apply to single or dual pack cartridges contained in an original HP package and shrink wrapped on a pallet for shipment by air.

ADR

Not regulated as dangerous goods.

IATA

Proper shipping name UN number

Magnetized Material

2807

IMDG

Not regulated as dangerous goods.

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

Labeling

Contains Amorphous silica, Iron oxide, polyester

All chemical substances in this HP product have been notified or are exempt from notification **Regulatory information**

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

16. OTHER INFORMATION

Other information This MSDS was prepared in compliance with EU Directive 91/155/EEC as amended by 2001/58/EC.

Disclaimer DISCLAIMER: This [Material] Safety Data Sheet is provided without charge to customers of

Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this and is believed to be accurate. It should not be construed as quaranteeing specific properties of the products as described or suitability for a particular

application. This was prepared to the requirements for and may not meet regulatory requirements

in other countries.

07-Aug-2012 **Issue date**

Manufacturer information Hewlett-Packard Company

> 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Material name: CE390A-X-XC-XD CE390A-X-XC-XD Version No.: 05 Revision date: 07-Aug-2012 Print date: 07-Aug-2012

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland open cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-term exposure limit

TCLP: <value> Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: CE390A-X-XC-XD

CE390A-X-XC-XD Version No.: 05 Revision date: 07-Aug-2012 Print date: 07-Aug-2012