

MATERIAL SAFETY DATA SHEET

1. Product and Company I	dentification		
Material name	HP LaserJet CF325X-XC Print Cartridge		
Version #	01		
Issue date	10-Dec-2013		
Product use	This product is a toner preparation that is used in HP LaserJet Enterprise M806/ HP LaserJel Enterprise flow MFP M830 series printers.		
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-5020 Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomer.inquiries@hp.com		
2. Hazards Identification			
Potential health effects			
Eyes	May cause transient slight irritation		
Skin	Unlikely to cause skin irritation.		
Inhalation	. Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.		
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.		
Other hazards	This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, as amended. None of the ingredients have been classified as carcinogens accord to EU, IARC, MAK, NTP, OSHA or ACGIH.		

3. Composition / Information on Ingredients

Non-hazardous components	CAS #	Percent
Polyester resin	Trade Secret	<55
Ferrite	Trade Secret	<50
Amorphous silica	7631-86-9	<3

4. First Aid Measures	
General advice	No information
First aid procedures	
Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Ingestion	Rinse mouth with water. Drink one to two glasses of water. If symptoms occur, consult a physician.
5. Fire Fighting Measures	
Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

able properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely
	dispersed in air.

Extinguishing media			
Suitable extinguishing media	CO2, water, or dry chemical		
Unsuitable extinguishing media	None known.		
Fire fighting equipment/instructions	If fire occurs in the printer, treat as an electrical fire.		
Specific methods	None established.		
Hazardous combustion products	Carbon monoxide and carbon dioxide.		
6. Accidental Release Measu	Ires		
Personal precautions	Minimize dust generation and accumulation.		
Environmental precautions	Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.		
Other information	Slowly vacuum or sweep the material into a bag or other sealed container. If a vacuum is used, the motor must be rated as dust explosion-proof. Clean remainder with a damp cloth or vacuum cleaner. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.		
7. Handling and Storage			
Handling	Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.		
Storage	Keep out of the reach of children. Store at room temperature. Keep tightly closed and dry. Store away from strong oxidizers.		
8. Exposure Controls / Perso	onal Protection		
Occupational exposure limits			
US. NIOSH: Pocket Guide			
Components	Type Value		
Components Amorphous silica (CAS 7631-86-9)	TypeValueTWA6 mg/m3		
Components Amorphous silica (CAS	Type Value		
Components Amorphous silica (CAS 7631-86-9)	TypeValueTWA6 mg/m3		
Components Amorphous silica (CAS 7631-86-9)	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3		
Components Amorphous silica (CAS 7631-86-9)	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.ertiesFine powder		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.ertiesFine powderSolid.		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state Form	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.ertiesFine powder Solid.solid		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state Form Color	Type Value TWA 6 mg/m3 USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3 Use in a well ventilated area. • t No personal respiratory protective equipment required under normal conditions of use. erties • Fine powder Solid. solid Black. Slight plastic odor Not applicable		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical state Physical state Form Color Odor pH Vapor pressure	Type Value TWA 6 mg/m3 USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3 Use in a well ventilated area. Image: Transmitted output to the equipment required under normal conditions of use. erties Fine powder Solid. Solid. Black. Slight plastic odor Not applicable Not applicable		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical state Physical state Form Color Odor pH Vapor pressure Boiling point	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica:USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.ertiesFine powderSolid.solidBlack.Slight plastic odorNot applicableNot applicableNot applicable		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical & Chemical Prop Appearance Physical state Form Color Odor pH Vapor pressure Boiling point Melting point/Freezing point	Type Value TWA 6 mg/m3 USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3 Use in a well ventilated area. * t No personal respiratory protective equipment required under normal conditions of use. erties * Fine powder * Solid * Black. * Slight plastic odor * Not applicable *		
Components Amorphous silica (CAS 7631-86-9) Exposure guidelines Engineering controls Personal protective equipment General 9. Physical state Physical state Form Color Odor pH Vapor pressure Boiling point	TypeValueTWA6 mg/m3USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)Amorphous silica:USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10 mg/m3Use in a well ventilated area.tNo personal respiratory protective equipment required under normal conditions of use.ertiesFine powderSolid.solidBlack.Slight plastic odorNot applicableNot applicableNot applicable		

Material name: CF325X-XC

Flash point

Not applicable

Viscosity	Not applicable	
Percent volatile	0 % estimated	
Softening point	212 - 302 °F (100 - 150 °C)	
VOC	Not available	
Other information	No information available	
Other data		
Decomposition temperature	> 392 °F (> 200 °C)	
10. Chemical Stability & Reactivity Information		
Chemical stability	Stable under normal storage conditions.	

•	
Conditions to avoid	Imaging Drum: Exposure to light
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.

11. Toxicological Information

Toxicological data			
Components	Species	Test Results	
Amorphous silica (CAS 7631-86-	9)		
Acute			
Oral			
LD50	Mouse	> 15000 mg/kg	
	Rat	> 22500 mg/kg	
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).		
Chronic effects	No information available.		
Carcinogenicity	Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).		
Serious eye damage/eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.		
Mutagenicity	Negative, does not indicate m	utagenic potential (Ames Test: Salmonella typhimurium)	
Reproductive effects	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65 and DFG (Germany).		
Further information	Complete toxicity data are not available for this specific formulation Refer to Section 2 for potential health effects and Section 4 for first aid measures.		

Ecotoxicological data Product		Species	Test Results
CF325X-XC			
Fish	LL50	Fish	> 1000 mg/l, 96 Hours
Ecotoxicity	LL50: > 1000	mg/l, Fish, 96.00 Hours	
Persistence and degradability	Not available.		

14. Transport Information DOT Not regulated as dangerous goo	UN2807		
14. Transport Information DOT Not regulated as dangerous goo IATA UN number UN proper shipping name IMDG	dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state and local regulations. HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle. ds.		
14. Transport Information DOT Not regulated as dangerous goo IATA UN number UN proper shipping name IMDG	of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle. ds. UN2807		
DOT Not regulated as dangerous goo IATA UN number UN proper shipping name IMDG	UN2807		
Not regulated as dangerous goo IATA UN number L UN proper shipping name I IMDG	UN2807		
IATA UN number UN proper shipping name IMDG	UN2807		
UN number UN proper shipping name IMDG			
UN proper shipping name			
IMDG	Magnetized Material		
5 5 5	ds.		
RID			
Not regulated as dangerous goods.			
ä	16 or more of these cartridges shipped together in a single package (e.g., box, container), by air, are regulated as a magnetized material. These requirements do not apply to single or dual pack cartridges contained in an original HP package and shrink wrapped on a pallet for shipment by air.		
15. Regulatory Information			
	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.		
Not regulated. DEA Exempt Chemical Mixtu Not regulated. TSCA Section 12(b) Export N	res Code Number Iotification (40 CFR 707, Subpt. D)		
Not regulated.			
CERCLA (Superfund) reportable None	quantity		
	authorization Act of 1986 (SARA)		
-	Immediate Hazard - No		
	Delayed Hazard - No		
	Fire Hazard - No Pressure Hazard - No		
	Reactivity Hazard - No		
SARA 302 Extremely	No		
SARA 311/312 T Hazardous chemical	No		
(All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.		
State regulations			
US. Massachusetts RTK - Sul	bstance List		
Not regulated.	andoue Substances		
US. Pennsylvania RTK - Haza Not regulated.	aruous Substances		

US. Rhode Island RTK

Not regulated.

16. Other Information	
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Disclaimer	This [Material] Safety Data Sheet is provided without charge to customers of Hewlett-Packarc Company. Data is the most current known to Hewlett-Packard Company at the time of preparatio of this (M)SDS and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application.
Other information	This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).
Issue date	10-Dec-2013
This data sheet contains changes from the previous version in section(s):	1. Product and Company Identification: Alternate Trade Names
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209
Explanation of abbreviations	

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
	-
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds